

Technical Data Sheet

Everlast

Description

Everlast Weather Proof is high quality acrylic based emulsion which provides a smooth flat finish. Product has excellent weather and scrub resistance.

Recommended use

Recommended for exterior / interior use on plaster, concrete, gypsum, brick work and asbestos surfaces where long lasting and washable finish is required.

Physical properties

| | |
|------------------|-----------------------|
| Colour | Standard Colour Range |
| Finish | Matt |
| Solids (vol %) | 44 ± 2 |
| Flash point | N/A- Water Based |
| Specific Gravity | 1.46 0.03 |

Film Thickness and Spreading Rate

| | |
|----------------------------|-----------------------|
| Film Thickness | 15 to 30 microns dft |
| Theoretical spreading rate | 15(m ² /l) |

Surface Preparation

All loose material including loose plaster, cement splashes, old paint, dust, etc. must be thoroughly removed. New plaster / concrete must be fully cured.

Application data

| | |
|--------------------|--|
| Application Method | Spray (airless or conventional), Brush, Roller |
| Thinner/Cleaner | Clean water |
| Thinning | 50 - 70% with Clean Water |

Drying Time

| Temperature | Dry to touch | Dry to handle | Recoating Time |
|-------------|--------------|---------------|----------------|
| 25 °C | 30 minutes | 2 hours | 3 hours |
| 35 °C | 15 minutes | 1 hour | 2 hours |

Typical paint system

On Plaster / Concrete

| | |
|--------------------------------|---------|
| Diamond Overall Wall Sealer | 1 Coat |
| Diamond Everlast Weather Proof | 2 Coats |

Everlast Weather Proof



Storage

The product must be stored in accordance to national regulations. The product should be kept in a well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing Size

4 Ltrs & 16 Ltrs

Health and Safety

Material health and safety datasheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.



The No. 1 Selling National Brand