

Technical Data Sheet

Ever Plus

Description

Diamond Ever Plus Putty is an economy-grade, good, performance interior putty designed to apply on rough and damaged surfaces to make the surfaces smooth.

Recommended Use

Diamond Ever Plus Putty is recommended to use as putty on concrete, cement, gypsum, hardboard, and brick surfaces for interior applications.

Physical Properties

Color	White
Finish	Matt
Solids (vol %)*	40 + 2
Flash point	none – water-based
Specific Gravity	1.50 – 1.60

Film Thickness and Spreading Rate

Recommended film thickness according to the surface (typically 100-300 microns)

Theoretical Spreading Rate according to film thickness (Normally 3-5 m²/kg/Coat)

Surface Preparation

All loose material including loose plaster, cement splashes, old paint, dust, etc. must be thoroughly removed. New plaster/ concrete must be fully cured.

Condition during application

The temperature of the substrate should be min. 3°C above the dew point of the air temperature and relative humidity not more than 70% measured in the vicinity of the substrate. Good ventilation is necessary when the paint is used in confined spaces. Mix the paint to uniform consistency before application.

Application Data

Application Method	By Putty knife / trowel / scraper.
Thinner/Cleaner	Clean water

Drying Time

Temperature	Dry to Touch	Dry to Handle	Recoating Time
25 °C-35 °C	1 hour	1 hour	4 hours

Typical Paint System

Diamond Water Based Primer	1 Coat
Diamond Ever Plus Putty	2 Coats
Diamond Emulsions Top Coat	2-3 Coats

Ever Plus Putty



Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from the heat and direct sunlight. The containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing Size

20 kg.

Health and Safety

Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist/vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.



Pakistan's No.1 Paint