

Technical Data Sheet

Everlast

Description

Diamond Everlast Woodcoat Thinner is a high quality fast drying thinner designed to dilute nitrocellulose based Paint, Wood Lacquer, Matt Lacquer and Sanding Sealer.

Recommended use

Designed to use as thinner for thinning Diamond Everlast High Gloss Enamel and Automotive paint to give rapid hardening & good adhesion.

Physical properties

Colour	Clear
Finish	NA
Solids (vol %)*	NA
Flash point	34 °C
Specific Gravity	0.80+/-0.02

Film Thickness and Spreading Rate

Spreading rate	(m ² /l) NA
----------------	------------------------

Surface Preparation	NA
---------------------	----

Everlast Woodcoat Thinner



Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing Size

1 Ltr, 4 Ltrs , 20 Ltrs & 200 Ltrs.

Health and Safety

Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.



The No. 1 Selling National Brand