Technical Data Sheet

Everlast

Description

Diamond Everlast Woodcoat Clear Varnish gives a high gloss finish. It is a high-build, transparent, tough and long-lasting film, which protects and decorates all types of interior wood, furniture, doors and windows etc.

Recommended Use

Suitable for exterior / interior wooden surfaces or where high gloss clear finish is required.

Physical Properties

ColourClearFinishGlossSolids (vol %)* 42 ± 2 Flash Point> $34 \,^{\circ}$ CSpecific Gravity90 - 95

Film Thickness and Spreading Rate

Film Thickness 30 microns dft

Spreading Rate 14-16 (m² / Ltr / Coat)

Surface Preparation

Ensure that surface is clean, dry and free from grease, oil and other contamination. Wood should be properly sanded.

Application data

Application Method Spray (airless or conventional), Brush, Roller.

Mixing Ratio (volume) Single Pack.

Thinner / Cleaner Mineral Turpentine.

Thinning 10-20 % Mineral Turpentine.

Drying Time

Temperature	Dry to Touch	Dry to Handle	Recoating Time
25 °C	4 hours	16 hours	16 hours
35 °C	3 hours	12 hours	12 hours

Typical Paint System

Diamond Everlast Woodcoat Clear Varnish 2 Coats

Everlast Woodcoat Clear Varnish



Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from heat and direct sunlight.

The containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing Size

3.64 Ltrs

Health and Safety

Material health and safety data sheet is available upon request. Please observe the precautionary notice displayed on the container. Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist/vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

